



Standard Dry Freight Quadcon Container, Double Doors On One Side, Roll Up Door On One Side

STANDARD FEATURES

- Corrugated steel sides, and roof
- Heavy-duty, aluminum roll up door on one side, ideal for on-board ship access
- Roll back door panels have no welded joints to crack or corrode
- Roll up door features continuous hinge panel joints designed to provide a water-tight seal for maximum cargo protection
- Belted rubber side seals on vertical track for additional weatherproofing
- Double Cargo doors on one side
- (8) Total wall tie down steel lashing bars, 2,000 lbs. cap., tested at 3,000 lbs. each
- 8 Columns Vertical E-Track (4 per side)
- Sheet metal ceiling cover plate
- Heavy duty steel floor
- 4-way fork lift pockets
- CSC Tested and Certified
- Connecting couplers, (3) per Quadcon
- Connecting coupler storage bracket, (1) each



OPTIONAL FEATURES

- Shelving
- Adaptor Plate for Removable Storage Modules
- Additional tie down features

OVERHEAD DOOR OPENING		
	HEIGHT	WIDTH
Ft in	5' 6-5/8"	4' 1-5/8"
Metric	1,692	1,261

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

SB812.RD	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft. in.	4' 9-7/16"	4' 7-3/4"	6' 10"	5' 10"	8' 0"	7' 7-5/16"	5' 11-3/16"	4' 5-5/8"
Metric	1,459	1,417	2,083	1,778	2,438	2,320	1,808	1,362
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs.	2,200		4,410		6,610		206 Cu. Ft.	
Kgs.	998		2,000		2,998		5.83Cu. M.	

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

SB812.RD

Standard Dry Freight Quadcon Container,
Double Doors On One Side, Roll Up Door On One Side

012924-R00

ISO 9001



CERTIFIED QUALITY
MANAGEMENT SYSTEM

GSA Advantage!